

SPECIFICATIONS AND FUNCTIONS

- 2-way normally closed solenoid valve.
- Normally closed, can direct operating without pressure.
- Available flu it: water, oil, gas, light, vacuum.
- Standard voltage: AC24V, 36V, 110V, 220V (50,60Hz).
DC12V, 24V, 110V.
- Voltage allowed: AC±10%, DC±1%.
- Connection: Thread to BS21

DESCRIPTION

- Working medium: Straight pull style film configuration.
- Form: Normally opened or Normally closed.
- Stuff: Complete copper or stainless steel.
- Differential pressure: 0~1MPa, 0.5-16MPa
- Working pressure: 1MPa, 1.6MPa
- Medium Temperature: -5°C ~ +80°C.
- Environment Temperature: -5°C ~ +60°C.
- Voltage: AC (380V, 220V, 110V, 36V, 24V).
DC (36V, 24V, 12V).



SPECIFICATIONS

Fig	Size(mm)	CV Value	Differential pressure (bar)	Power (VA)
804-08	8	0.23	0.5-16	8
804-10	10	0.6	0.5-16	14
804-15	15	4.8	0.5-16	14
804-20	20	7.6	0.5-16	14
804-25	25	12	0.5-16	14
804-32	32	24	0.5-12	50
804-40	40	29	0.5-12	50
804-50	50	48	0.5-12	50

► **Note:** Design and specifications are subject to change without prior notice.