

BRASS BIBCOCK FIG.122 & TAP FIG.123, PN10

SPECIFICATION

THREADED TO BS21, ISO7, ASMEB1.20.1





PRESSURE/TEMPERATURE RATINGS

Working Pressure	10 bar Water Non Shock
Testing Pressure	Shell: 15 bar, Hydrostatic Seat: 11 bar, Hydrostatic
Working Temperature	-10°C ~80°C

MATERIALS

Part	Material	ASTM	BS 5154
Body/Cap	Brass	B124 C37700	2874 CZ122
Ball	Brass	B124 C37700	2874 CZ122
Stem	Brass Rod	B16 C36000	2874 CZ121
Handle	Brass Rod	B16 C36000	2874 CZ121

PICTURE & SIZE

Picture	Fig	Size (inch)	Material	W.P (bar)	Weight(g)
	Fig.122.1	1/2" 3/4"	Brass Cu57-3	10	93 190
Bibcock with union					
	Fig.122.2	1/2" 3/4"	Brass Cu57-3	10	89 185
Bibcock					
	Fig.123.1	1/2" 3/4"	Brass Cu57-3	10	98 185
Tap with hose union					
	Fig.123.2	1/2" 3/4"	Brass Cu57-3	10	86 180
Tap					

► **Note:** Design and specifications are subject to change without prior notice.